

<b>EFMB Test Score Sheet</b> <b>WARRIOR SKILLS — DISASSEMBLE, ASSEMBLE, AND PERFORM A FUNCTIONS CHECK ON AN M4 SERIES CARBINE OR M16 SERIES RIFLE</b> (For use of this form, see AMEDDC&S HRCOE Pam 350-10, the proponent is MCCS-OPE)		
CANDIDATE'S RANK AND NAME	CANDIDATE #	
<b>TASK:</b> DISASSEMBLE, ASSEMBLE, AND PERFORM A FUNCTIONS CHECK ON AN M4 SERIES CARBINE OR M16 SERIES RIFLE.		
<b>CONDITIONS:</b> Given an M4 series carbine or M16 series rifle and a magazine.		
<b>STANDARDS:</b> Clear, disassemble, assemble, and perform a function check on an M4 series carbine or M16 series rifle and ensure that the weapon operated properly with the selector switch in each position within 4 minutes.		
<b>NOTE: THIS TASK HAS BEEN MODIFIED FOR EFMB TESTING PURPOSES ONLY.</b>		
PERFORMANCE STEPS/MEASURES	GO	NO-GO
1. Clear the weapon prior to disassembly.		
<b>NOTE: Time begins when the candidate touches the weapon.</b>		
<b>NOTE:</b> The magazine will initially be in the weapon.		
a. Point the weapon in a safe direction.		
b. Attempt to place the selector lever on SAFE.		
<b>NOTE:</b> The selector cannot be turned to "SAFE" unless the weapon is cocked.		
c. Remove the magazine from the weapon, if present.		
d. Lock the bolt open.		
(1) Pull the charging handle rearward.		
(2) Press the bottom of the bolt catch.		
(3) Allow the bolt to move forward until it engages the bolt catch.		
(4) Return the charging handle to the forward position.		
e. Check the receiver and chamber to ensure that they do not contain ammunition.		
2. Disassemble the weapon into 13 parts.		
<b>NOTE:</b> There is no required sequence for disassembly.		
a. Remove the sling.		
b. Push the takedown pin as far as it will go and pivot the upper receiver from the lower receiver.		
c. Push the receiver pivot pin.		
d. Separate the upper and lower receivers.		
e. Pull back the charging handle.		
f. Remove the bolt carrier and bolt.		
g. Remove the charging handle.		
h. Remove the firing pin retaining pin.		

AMEDDC&S HRCOE PAM 350-10

i. Put the bolt assembly in the locked position by pushing in the bolt.		
j. Remove the firing pin by allowing it to drop out of the rear of the bolt carrier into your hand.		
k. Remove the bolt cam pin by turning it one-quarter turn and lifting it out.		
l. Pull the bolt assembly from the carrier.		
m. Remove the extractor pin by pushing it out with the firing pin (use care not to damage the firing pin).		
n. Lift out the extractor and spring, taking care that the spring does not separate from the extractor.		
o. Release the buffer by pressing the buffer and depressing the retainer.		
p. Remove the buffer and action spring separating the buffer from the spring.		
3. Assemble the weapon.		
NOTE: There is no required sequence for assembly.		
a. Insert action spring and buffer.		
b. Insert extractor and spring.		
c. Push in extractor pin.		
d. Slide bolt into carrier.		
<b>WARNING: BE SURE THAT THE CAM PIN IS INSTALLED IN THE BOLT GROUP. IF IT IS NOT, THE WEAPON CAN STILL FIRE AND MAY EXPLODE.</b>		
e. Replace bolt cam pin.		
f. Drop in and seat firing pin.		
g. Pull bolt back.		
h. Replace retaining pin.		
i. Engage, then push charging handle in part of the way.		
j. Slide in bolt carrier group.		
k. Push in charging handle and bolt carrier group together.		
l. Join upper and lower receivers.		
m. Engage receiver pivot pin.		
n. Close upper and lower receiver groups. Push in takedown pin.		
o. Replace the sling.		
NOTE: If candidate inserts magazine, they will have to remove it to perform the function check.		
4. Check an M4 series carbine or M16 series rifle with the selector lever in the "SAFE" position.		
a. Pull the charging handle to the rear and release it.		
b. Place the selector lever in the "SAFE" position.		
c. Pull the trigger (the hammer should not fall).		
5. Check an M4 series carbine or M16 series rifle with the selector lever in the "SEMI" position.		
a. Place the selector lever in the "SEMI" position.		

b. Pull the trigger, holding it to the rear (the hammer should fall).		
c. Continue to hold the trigger to the rear while pulling the charging handle to the rear and releasing the charging handle.		
d. Release the trigger with a slow, smooth motion until the trigger is fully forward (the hammer should not fall).		
e. Pull the trigger (the hammer should fall).		
NOTE: For weapons with "AUTO", skip to step 7.		
6. Check an M4 series carbine or M16 series rifle with the selector lever in the "BURST" position.		
a. Place the selector lever in the "BURST" position.		
b. Pull the charging handle to the rear and release it.		
c. Pull the trigger, holding it to the rear (the hammer should fall).		
d. While holding the trigger to the rear, pull the charging handle to the rear and release the charging handle three times.		
e. Release the trigger.		
f. Pull the trigger (the hammer should fall).		
7. Check an M4 series carbine or M16 series rifle with the selector lever in the "AUTO" position.		
a. Pull the charging handle to the rear and release it.		
b. Pull the trigger (the hammer should fall).		
c. Hold the trigger to the rear and cock the weapon.		
d. Fully release the trigger then pull it to the rear again; the hammer should not fall.		
8. Inform the evaluator of any malfunction of the weapon during the function check.		
9. Insert magazine (Time ends).		
10. Complete all required performance steps/measures within 4 minutes.		
11. Met all administrative requirements for this task.		
<b>EVALUATOR WRITES: CANDIDATE'S TIME FOR TASK:</b>		
REASON(S) FOR FAILURE	DOES THE CANDIDATE WISH TO REBUT THIS TASK? (CANDIDATE INITIALS APPROPRIATE BOX)	YES NO
LANE OIC/NCOIC INITIALS	EVALUATOR'S SIGNATURE	DATE