

AMEDDC&S HRCOE PAM 350-10

<b>EFMB Test Score Sheet</b> <b>WARRIOR SKILLS — DISASSEMBLE, ASSEMBLE, AND PERFORM A FUNCTIONS CHECK ON AN M9 PISTOL</b> (For use of this form, see AMEDDC&S HRCOE Pam 350-10, the proponent is MCCS-OPE)		
CANDIDATE'S RANK AND NAME	CANDIDATE #	
<b>TASK:</b> DISASSEMBLE, ASSEMBLE, AND PERFORM A FUNCTIONS CHECK E AN M9 PISTOL.		
<b>CONDITIONS:</b> Given an M9 pistol and a magazine.		
<b>STANDARDS:</b> Clear, disassemble, and assemble an M9 pistol and perform a function check within 3 minutes.		
<b>NOTE: THIS TASK HAS BEEN MODIFIED FOR EFMB TESTING PURPOSES ONLY.</b>		
PERFORMANCE STEPS/MEASURES	GO	NO-GO
1. Clear the pistol prior to disassembling the pistol.		
<b>NOTE: Time begins when candidate begins any step/measure listed below.</b>		
<b>NOTE:</b> The lever will initially be set in the "FIRE" position and an empty magazine will be in the pistol.		
a. Place the safety lever in the "SAFE" position.		
b. Depress the magazine release button; remove the magazine from the pistol.		
c. Pull the slide to the rear.		
d. Push the slide stop up, locking the slide to the rear.		
e. Look into the chamber to ensure that it is empty.		
2. Disassemble the pistol.		
a. Depress the slide stop and let the slide go forward.		
b. With your right hand, hold the pistol with the muzzle slightly raised.		
c. With your forefinger, press the disassembly lever button.		
d. Rotate the disassembly lever downward until it stops.		
e. Pull the slide and barrel assembly forward and remove it from the receiver.		
f. Slightly compress the recoil spring and spring guide. At the same time, lift them up and remove them, allowing the recoil spring to stretch slowly.		
g. Separate the recoil spring from the spring guide.		
h. Push in on the locking block plunger while pushing the barrel forward slightly. Lift and remove the locking block and barrel assembly from the slide.		
3. Assemble the pistol.		
a. Grasp the slide with the bottom facing up.		
b. With the other hand, grasp the barrel assembly with the locking block facing up.		
c. Insert the muzzle into the forward end of the slide. At the same time, lower the rear of the barrel assembly by moving the barrel slightly downward with light thumb pressure. The barrel will fall into place.		
d. Insert the recoil spring guide into the recoil spring.		
e. Insert the end of the recoil spring and the recoil spring guide into the recoil spring housing. At the same time, compress the recoil spring and lower the spring guide until it is fully seated on the locking block cutaway.		
<b>CAUTION:</b> BE SURE THAT THE HAMMER IS UNCOCKED AND FIRING PIN BLOCK LEVER IS IN THE DOWN POSITION. IF THE HAMMER IS COCKED, CAREFULLY AND MANUALLY LOWER THE HAMMER. DO NOT PULL THE TRIGGER WHILE PLACING THE SLIDE ONTO THE RECEIVER.		

f. Push the firing pin block lever down. Grasp the slide and barrel assembly, with the sights up and align the slide on the receiver assembly guide rails.				
g. Push until the rear of the slide is a short distance beyond the rear of the receiver assembly and hold. At the same time, rotate the disassembly latch lever upward. A click indicates a positive lock.				
4. Perform a function check.				
a. Insert an empty magazine into the pistol and ensure that the magazine catch locks the magazine in place.				
b. Retract the slide and release it. The magazine follower should push up on the slide stop, locking the slide to the rear.				
c. Depress the magazine release button allowing the magazine to fall free.				
d. Ensure that the decocking/safety lever is in the safe (down) position. Depress the slide stop allowing the slide to return fully forward. At the same time, the hammer should fall to the full forward position.				
e. Pull and release trigger. Firing pin block should move up and down.				
f. Place decocking/safety lever in fire (up) position.				
g. Pull trigger to check double action. Hammer should cock and fall.				
h. Pull trigger again and hold to rear. Manually retract and release slide while holding trigger to the rear. Release trigger, click should be heard, hammer should not fall.				
i. Pull trigger to check single action. Hammer should fall.				
5. Correctly perform all performance steps/measures within 3 minutes.				
6. Met all administrative requirements for this task.				
<b>EVALUATOR WRITES: CANDIDATE'S TIME FOR TASK:</b>				
REASON(S) FOR FAILURE	DOES THE CANDIDATE WISH TO REBUT THIS TASK? (CANDIDATE INITIALS APPROPRIATE BOX)	<table border="1"> <tr> <td>YES</td> <td>NO</td> </tr> </table>	YES	NO
YES	NO			
<p>LANE OIC/NCOIC INITIALS</p> <p>EVALUATOR'S SIGNATURE</p>		DATE		